

PRODUCT DATA SHEET

PHOS COPPER ANODES

QUALITY SYSTEM CERTIFIED TO ISO 9001:2008

IMC 352 - PH	PRODUCT SPECIFICATION IMC 352 - PHOS COPPER C12220		
Copper ⁽¹⁾	99.95 MIN%	J TOTOT	
Iron	0.003 MAX%		
Sulfur	0.003 MAX%	SIZES	PACKAGING
Lead	0.002 MAX%	PHOS COPPER BALLS	• 44 lb Boxes / 2
Antimony	0.002 MAX%	19mm / .75"	2200 lb Pallet
Nickel	0.002 MAX%	25mm / 1.00"	• 220 lb Drums
Arsenic	0.001 MAX%	31mm / 1.25"	1980 lb Pallet
Tin	0.002 MAX%	40mm / 1.60"	• 50 lb Pails / 2
Total Other ⁽²⁾	0.010 MAX%	45mm / 1.80"	1600 lb Pallet
Phosphorus	0.040 - 0.065 %	48mm / 1.90" 50mm / 2.00"	Bulk Packaging



•	44 lb	Boxes / 20 Kg
	2200	Ib Pallets / 1000 Kg

- / 100 Kg ets / 900 Kg
- 22.7 Kg ets / 726 Kg
- ng Available

(1) Copper includes Silver and Phosphorus

(2) Other metallic elements include: Bi, Cd, Mn, Hg, Se, Te, Zn

FEATURES

- · Hot rolling produces a fine-grained structure.
- Uniform Phos distribution reduces sludging.
- · Consistent surface area and consistent dissolution.
- Quick-settling characteristics avoid bridging, voids and basket damage.
- Perfect for automated chute loading.
- For use in any anode basket or tray.
- Special process eliminates precleaning.
- · Color-coded, user-friendly packaging.
- · Certificate of Analysis issued for every lot.

TYPICAL APPLICATIONS

• Printed Circuits

55mm / 2.20"

- Plated on Plastic Trim
- Decorative Plating
- Electronic Components
- Corrosion Protection in Automotive Parts
- Electrical Connectors
- Power Distribution Equipment
- Ammunition
- Coinage
- Rotogravure Cylinders

CAS NUMBER: 7440 - 50-8 / MSDS NUMBER: 2007

This information herein is believed to be reliable, however, no warranty, expressed or implied, is made as to its accuracy or completeness and none is made as to the fitness of this material for any purpose. The manufacturer shall not be liable to damages to person or property resulting from its use. Nothing herein shall be construed as a recommendation for use in violation of any patents.

> 135 Old Boiling Springs Road • Shelby, NC 28152 Phone: 704.482.8200 • Fax: 704.482.8038 www.imc-ma.com sales@imc-ma.com