

Outline

Model	Output	Outline (mm)										Weight (kg)	Output terminal
		A	B	C	D	E	A1	A2	C1	C2			
MRS-12 005	12V- 500A	300	500	700	240	340	60	100	305	400	79	(1)	
MRS-12 005PR							150	190	290	500	85	(1)	
MRS-12 010	12V- 1000A	330	550	850	270	390	155	230	355	635	130	(2)	
MRS-12 010PR							220	295	475	640	150	(2)	
MRS-12 015	12V- 1500A	330	550	850	270	390	155	230	355	635	150	(3)	
MRS-12 015PR							220	295	475	640	250	(3)	
MRS-12 020	12V- 2000A	450	650	1100	390	490	220	295	475	640	200	(4)	
MRS-12 020PR							290	375	560	840	250	(4)	
MRS-12 030	12V- 3000A	450	650	1100	390	490	220	295	475	640	255	(5)	
MRS-12 030PR							290	375	560	840	300	(5)	
MRS-12 040	12V- 4000A	530	700	1450	470	540	185	265	560	840	380	(6)	
MRS-12 040PR							260	340	560	840	450	(6)	
MRS-12 050	12V- 5000A	530	700	1450	470	540	185	265	560	840	420	(6)	
MRS-12 050PR							260	340	560	840	480	(7)	
MRS-12 060	12V- 6000A	650	950	1450	550	790	230	400	640	900	630	(7)	
MRS-12 070	12V- 7000A	700	1000	1550	600	840	240	440	710	1025	850	(8)	
MRS-12 080	12V- 8000A	700	1000	1550	600	840	240	440	710	1025	920	(8)	
MRS-12 100	12V-10000A	700	1000	1550	600	840	240	440	710	1025	1000	(9)	
MRS-12 120	12V-12000A	800	1100	1750	700	940	290	490	785	1125	1100	(9)	
MRS-12 150	12V-15000A	800	1100	1750	700	940	290	490	785	1125	1500	(10)	

Changed to 8 for 8V output. Changed to 15 for 15V output

